PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5:

A1

(11) International Publication Number:

WO 91/14745

C09D 167/00, C08G 63/18

(43) International Publication Date:

3 October 1991 (03.10.91)

(21) International Application Number:

PCT/GB91/00450

(22) International Filing Date:

26 March 1991 (26.03.91)

(30) Priority data:

The state of the s

9006737.2

26 March 1990 (26.03.90)

GB

(71) Applicant (for all designated States except US): COUR-TAULDS COATINGS (HOLDINGS) LIMITED [GB/ GB]; 18 Hanover Square, London W1A 1AD (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): O'KEEFFE, Luke, James [GB/GB]; 183 Wingrove Road, Fenham, Newcastle upon Tyne NE4 9DA (GB). NIXON, Steven, Alistair [GB/GB]; 17 Glenwood Walk, Chapel Park, Newcastle upon Tyne NE5 1ST (GB). CAMERON, Colin [GB/GB]; 140 Normount Road, Newcastle upon Tyne NE4 8SJ (GB). PENMAN, Alan, Keith [GB/GB]; 8 Friarside Crescent, Rowlands Gill, Tyne & Wear NE39 1DQ (GB).

(74) Agents: SENIOR, Janet et al.; Abel & Imray, Northumberland House, 303-306 High Holborn, London WC1V 7LH (GB).

(81) Designated States: AT (European patent), AU, BE (European patent), BR, CA, CH (European patent), DE (European patent), DK (European patent), ES (European patent), FI, FR (European patent), GB (European patent) tent), GR (European patent), HU, IT (European patent), JP, KR, LU (European patent), NL (European patent), NO, PL, SE (European patent), SU, US.

Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

4) Title: COATING COMPOSITIONS

(57) Abstract

A thermosetting powder coating composition according to the present invention comprises as binder a co-reactable particulate mixture of a carboxylic acid-functional polyester component and a curing agent having groups reactive with carboxylic acid groups, characterized in that the carboxylic acid-functional component comprises a semi-crystalline polyester having an acid value of from 10 to 70 mg KOH/g and a hydroxy value of no more than 11 mg KOH/g. Generally the semi-crystalline polyester has one or more Tg values less than 55 °C, a sharp melting point of 50 to 200 °C and preferably a number average molecular weight of at least 1600. The composition may, if desired, include an amorphous polyester and the curing agent may be, for example, an epoxy resin or a bis(beta-hydroxyalkylamide). Coating compositions of the invention cure faster than in the absence of semi-crystalline polyesters and the thermoset coatings prepared therefrom have improved appearance and mechanical properties (especially flexibility).

CLAIMS

1. A th rmosetting powder coating composition comprising as binder a co-reactable particulate mixtur of a carboxylic acid-functional polyester c mponent and a curing agent having groups reactive with carboxylic acid groups, characterised in that the carboxylic acid-functional component comprises:

5

10

- (A) 5-100% by weight of at least one semi-crystalline polyester having an acid value of from 10 to 70 mg KOH per gram and a hydroxy value of no more than 11 mg KOH per gram; and
- (B) 0-95% by weight of at least one amorphous polyester having a Tg of at least 30°C and an acid number of 15 to 90.
- 2. A composition according to claim 1, characterised in that the binder comprises 40-98% by weight of the carboxylic acid-functional polyester component and 2-60% by weight of the curing agent.
- A composition according to claim 1 or 2, characterised in that the semi-crystalline polyester has a number average molecular weight of 1600 to 12,000.
 - 4. A composition according to claim 3, characterised in that the semi-crystalline polyester has a number average molecular weight of 2500 to 4500.
- 5. A composition according to any of claims 1 to 4, characterised in that the semi-crystalline polyester has an acid value of 28 to 45.
 - 6. A composition according to any of claims 1 to 5, characterised in that the semi-crystalline polyester has a hydroxy value of no more than 5.

7. A composition according to any of claims 1 to 6, characteris d in that the semi-crystalline polyester has a melt viscosity of from 0.1 to 7 Pa s (1 to 70 p ise) at 200°C and from 4 to 20 Pa s (40 to 200 pois) at 160°C.

\$

- 8. A composition according to any of claims 1 to 7, characterised in that the carboxylic acid-functional polyester component comprises 5 to 90% by weight of semi-crystalline polyester (A) and 10-95% by weight of amorphous polyester (B).
- 9. A composition according to claim 8, characterised in that the carboxylic acid-functional polyester component comprises 10-40% by weight of semi-crystalline polyester (A) and 60-90% by weight of amorphous polyester (B).
- which the amorphous polyester is based on a condensation reaction of a polyol component comprising one or more aliphatic or cycloaliphatic polyols with an acid component comprising one or more aliphatic, cycloaliphatic or aromatic polycarboxylic acids or an anhydride, ester or acid chloride thereof, characterised in that at least 10% by weight of the acid component is isophthalic acid.
 - 11. A composition according to claim 10, characterised in that at least 40% by weight of the acid component is isophthalic acid.
- 25 12. A composition according to any of claims 1 to 11, characterised in that the curing agent is a polyepoxide and the molar ratio of epoxide groups in the curing agent to carboxylic acid groups in the polyester component is 0.6 to 1.6:1.
- 13. A composition according to claim 12, characterised in that the polyepoxid is an epoxy r sin of epoxide equivalent weight 150-1000 and the weight ratio of

epoxy r sin to polyest r component is 15:85 to 60:40.

- 14. A composition according to claim 12, characterised in that the curing agent is a solid non-resinous polyep xide.
- 15. A composition according to any of claims 1 to 11, characterised in that the curing agent is a bis(beta-hydroxyalkylamide).
- 16. A semi-crystalline polyester for use in thermosetting powder coatings with one or more Tg values less than 55°C, a sharp melting point of 50°C to 200°C, an acid value of from 10 to 70 mg KOH per gram and a hydroxy number of no more than 11 mg KOH per gram.
- 17. A semi-crystalline polyester according to claim 16, characterised in that it has a number average molecular weight of at least 1600.
 - 18. A semi-crystalline polyester according to claim 16 or claim 17, characterised in that it has a number average molecular weight of up to 12,000.
- 19. A semi-crystalline polyester according to claim 20 18, characterised in that it has a number average molecular weight of 2500 to 4500.
 - 20. A semi-crystalline polyester according to any of claims 16 to 19, characterised in that it has an acid value of 28 to 45.
- 21. A semi-crystalline polyester according to any of claims 16 to 20, characterised in that it has a hydroxy value of no more than 5.
 - 22. A semi-crystalline polyester according to any of claims 16 to 21, characterised in that it has a melt

viscosity f from 0.1 to 7 Pa s (1 to 70 pois) at 200°C and from 4 to 20 Pa s (40 to 200 pois) at 160°C.

23. A proc ss for th preparation of a thermosetting powder coating composition, characteris d in that a coreactable particulate mixture of a carboxylic acid-functional polyester component as defined in claim 1, a curing agent and optionally one or more pigments and/or other additive(s) is blended and comminuted.

5

₹

5

- 24. A process according to claim 23, characterised in that after melting in the blending step the semi-crystalline polyester is recrystallised by an annealing treatment.
 - 25. A thermosetting powder coating composition prepared according to claim 23 or claim 24.
- line polyester for use in thermosetting powder coatings, by polycondensation between one or more suitable polyols and one or more suitable polycarboxylic acid components selected from acids, anhydrides, esters and acid halides, characterised in that excess of acid over alcohol is used to give a product having an acid value of from 10 to 70 mg KOH/g and a hydroxy value of no more than 11 mg KOH/g.
 - 27. A semi-crystalline polyester prepared according to claim 26.
- 28. A process for coating a substrate characterised in that the thermosetting powder coating composition of any of claims 1 to 15 or claim 25 is applied to the substrate and is heated on the substrate to fuse and cure the coating.
 - 29. A substrate when coated by a process according to claim 28.

INTERNATIONAL SEARCH REPORT

International Application No PCT/GB 91/00450

I. CLAS	SIFICATION F SUBJECT MATTER (if several classification symbols apply, indicate all)	1/GB 91/00450
Accordin	g to International Patent Classification (IPC) or to both National Classification and IPC	
IPC ⁵ :	C 09 D 167/00, C 08 G 63/18	·
II. FIELD	S SEARCHED	
Classificati	Minimum Documentation Searched 7	
Ciassinicati	ion System Classification Symbols	
IPC ⁵	C 09 D, C 08 G	
	Documentation Searched other than Minimum Documentation to the Extent that such Documents are included in the Fields Searched •	
III. D. CI	UMENTS CONSIDERED TO BE RELEVANT!	
Category *		
	i with minication, where appropriate, or the relevant passages is	Relevant to Claim No. 13
x	US, A, 4217426 (R.L. McCONNELL) 12th August 1980 see claims 1-8	16
	cited in the application	
х	GB, A, 2189498 (U.C.B) 28th October 1987 see claims 1-23	26,27
A		1
A	EP, A, 0322834 (PPG INDUSTRIES) 5th July 1989 see claims 1-5	1,2,15
Α	CH, A, 614733 (INVENTA AG) · 14th December 1979 see claims 1-3	1
	./	
"A" doc con "E" earl filin "L" doc whi cita "O" doc oth "P" doc late	al categories of cited documents: 10 "T" later document published after	nflict with the application but iple or theory underlying the ance; the claimed invention or cannot be considered to ance; the claimed invention re an inventive step when the ne or more other such docug abvious to a person skilled
	Actual Completion of the International Search Date of Mailing of this International	Search Report
	18th July 1991 30.08.91	
Internation	al Searching Authority Signature of Authorized Officer M. PEIS:	
	EUROPEAN PATENT OFFICE	Yes 1

X .

edath .	Cilation of Document, " with Indication, where appropriate, of the relevant passages	Relevant to Claim No.	
A	EP, A, 0010805 (UNILEVER NV) 14th May 1980 see claim: 1; page 3, lines 19-23	1	
A	EP, A, 0038635 (DAINIPPON INK AND CHEMICALS, INC.) 28th October 1981 see claims 1-10	1	
A	WO, A, 89105320 (EASTMAN KODAK) 15th June 1989 see claim 1 cited in the application	1	
		·	

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.

GB 9100450 SA 46162

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on 26/08/91

The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
US-A- 4217426	12-08-80	US-A-	4155952	22-05-79
GB-A- 2189498	28-10-87	CA-A- US-A-	1273739 4740580	04-09-90 26-04-88
EP-A- 0322834	05-07-89	US-A- JP-A-	4801680 2003458	31-01-89 09-01-90
CH-A- 614733	14-12-79	None		
EP-A- 0010805	14-05-80	NL-A- AT-T- BE-A- US-A-	7810813 674 879782 4340698	02-05-80 15-02-82 30-04-80 20-07-82
EP-A- 0038635	28-10-81	JP-A- US-A-	56136856 . 4499239	26-10-81 12 - 02-85
WO-A-89105320		None		